



Product Information

COBRA CHASSIS GREASE GOLD

COBRA CHASSIS GREASE GOLD is a calcium soap thickened with mineral oil base. It applicable on automotive, industrial application, water pumps bearing and roller bearing. Water resistance is one of the advantage of this product. COBRA CHASSIS GREASE GOLD applicable on wet media and help the machine to have a good rotation. Premium mineral oil based on this product has adhesive property and it is a safe product to be use.

APPLICATIONS

- Uses in automotive and industrial applications.
- Lubricants under moderate load, speed, and temperature.
- Industrial plain and roller bearing.
- Water pumps bearing.
- Industrial grease cup application.

BENEFITS

- Premium quality of mineral oil.
- Excellent water resistance.
- Remarkable pump-ability.
- Adheres firmly to metal surface.
- Exquisite stable performance.
- Minimum dropping point at 109°C.
- Outstanding protection against rust and corrosion.

TYPICAL PROPERTY

CHARACTERISTIC	METHOD	RESULTS
Thickener		Calcium
Color		Brown
Texture		Fibrous
NLGI Consistency		3
Penetration Point at 25°C	ASTM D-217	210
Dropping Point (°C)	ASTM D-2265	109
Viscosity Kinematics @ 100°C, cSt	ASTM D-445	14.5

PACKAGING

24X1LB, 15KG NLGI: 3





Informasi Produk

COBRA CHASSIS GREASE GOLD

COBRA CHASSIS GREASE GOLD adalah *calcium soap thickened* dengan menggunakan bahan dasar *mineral oil*. Produk ini cocok digunakan untuk kendaraan pribadi, kendaraan industri, alat-alat berat pada perindustrian, bantalan pompa air dan *roller bearing*. COBRA CHASIS GREASE GOLD memiliki keunggulan dalam hal *water resistance* sehingga dapat digunakan pada media basah sekalipun dan membuat mesin dapat berotasi lebih baik. Selain itu, dengan bahan dasar *mineral oil*, produk ini memiliki sifat perekat yang baik dan aman untuk digunakan.

PENGUNAAN

- Dapat digunakan pada kendaraan pribadi dan industri.
- Peluman dengan beban, kecepatan dan suhu sedang.
- Bantalan polos dan *roller bearing*.
- Bantalan pompa air.
- Diaplikasikan untuk keperluan industri.

KEUNGGULAN

- Menggunakan bahan dasar *mineral oil* premium.
- Kualitas *water resistant* terbaik.
- Membuat rotasi lebih mudah.
- Melekat kuat pada permukaan logam.
- Unggul dalam menjaga stabilitas performa alat.
- Minimal *dropping point* pada suhu 109°C.
- Mencegah korosi dan karat.

TYPICAL PROPERTY

CHARACTERISTIC	METHOD	RESULTS
Thickener		Calcium
Color		Brown
Texture		Fibrous
NLGI Consistency		3
Penetration Point at 25°C	ASTM D-217	210
Dropping Point (°C)	ASTM D-2265	109
Viscosity Kinematics @ 100°C, cSt	ASTM D-445	14.5

KEMASAN

24X1LB, 15KG NLGI: 3

