



Product Information

COBRA CHASSIS GREASE GREEN

COBRA CHASSIS GREASE GREEN is one of the multi-purpose grease formulated with a calcium thickener and high viscosity base oils. The special selected tackiness agent will help the COBRA Chassis Greases to cling firmly to the moving parts such as ball joints, chassis and U-joints in the automotive and farm equipment.

APPLICATIONS

COBRA CHASSIS GREASE GREEN is applicable on tractor, automotive both in commercial and passenger, also applicable on earth-moving equipment such as bulldozer, excavator, backhoe, skid-steer loader and others. It is excellent for chassis points, shackles, bushings, clutch throw-out bearings and similar applications.

BENEFITS

- High viscosity base oil.
- Excellent water resistance.
- Smooth and tacky texture.
- Remarkable pump-ability.
- Adheres firmly to metal surface.
- Exquisite stable performance.
- Minimum dropping point at 102°C.

TYPICAL PROPERTY

CHARACTERISTIC	METHOD	RESULTS	RESULTS	RESULTS
		1	2	3
NLGI Grade				
Thickener Type		Calcium		
Color		Dark Green		
Texture		Smooth, Tacky		
Penetration Point at 25°C	ASTM D-217	315	275	230
Dropping Point (°C)	ASTM D-2265	98	102	102
Viscosity Kinematics @ 100°C, cSt	ASTM D-445	15 - 25	15 - 25	15 - 25

PACKAGING

24X1LB, 10LB, 15KG NLGI: 3





Informasi Produk

COBRA CHASSIS GREASE GREEN

COBRA CHASSIS GREASE HIJAU adalah pelumas gemuk serba guna yang diformulasikan dengan *calcium soap thickener* dan *base oil* viskositas tinggi. COBRA CHASSIS GREASE HIJAU dengan formula khusus akan melekat kuat dan memberikan kemudahan rotasi di bagian-bagian seperti *ball joints*, *chassis* dan *U-joints* pada kendaraan dan alat pertanian.

PENGGUNAAN

COBRA CHASSIS GREASE HIJAU dapat digunakan pada traktor, kendaraan pribadi maupun kendaraan umum serta alat berat seperti buldoser, ekskavator, *backhoe*, *skid-steer loader*, dan lainnya. Pelumas gemuk ini dapat digunakan untuk memberikan performa optimal pada bagian *chassis points*, *shackles*, *bushings*, *clutch throw-out bearings* dan bagian lainnya yang serupa.

KEUNGGULAN

- Viskositas tinggi.
- Kualitas *water resistant* terbaik.
- Memiliki tekstur yang lembut dan lengket.
- Membuat rotasi lebih mudah.
- Melekat kuat pada permukaan logam.
- Unggul dalam menjaga stabilitas performa alat.
- Minimal *Dropping point* pada suhu 102°C.

TYPICAL PROPERTY

CHARACTERISTIC	METHOD	RESULTS	RESULTS	RESULTS
NLGI Grade		1	2	3
Thickener Type		Calcium		
Color		Dark Green		
Texture		Smooth, Tacky		
Penetration Point at 25°C	ASTM D-217	315	275	230
Dropping Point (°C)	ASTM D-2265	98	102	102
Viscosity Kinematics @ 100°C, cSt	ASTM D-445	15 - 25	15 - 25	15 - 25

KEMASAN

24X1LB, 10LB, 15KG NLGI: 3

