



Product Information

COBRA CALCIUM MULTIPURPOSE GREASE MERIGOLD NO 3

COBRA CALCIUM MULTIPURPOSE GREASE MERIGOLD NO 3 is the perfect choice to support your operations with dependable protection and long-lasting performance.

APPLICATIONS COBRA CALCIUM MULTIPURPOSE GREASE MERIGOLD NO 3 is a versatile, high-consistency calcium-based grease, carefully crafted to provide reliable lubrication and exceptional protection for a wide range of industrial, construction, automotive, and agricultural applications. This product has minimum dropping point at 147°C.

- BENEFITS**
- Minimum dropping point at 147°C
 - Superior corrosion protection
 - Smooth texture that lasts longer
 - Thick and maintain its original shape
 - Versatility across applications
 - Performance capability equivalent to 70% of Lithium Grease
 - Translucent Golden appearance

TYPICAL PROPERTY

CHARACTERISTIC	METHOD	RESULTS
Thickener		Calcium
Color Visual		Translucent Gold
Texture		Smooth
NLGI Consistency		3
Worked Cone Penetration (25°)(0.1mm)	GB/T 269	225
Dropping Point (°C)	GB/T 4929	147
Stell mesh oil separation (%)	SH/T 0324	1.3
Copper corrosion (100°C, 24h)	GB/T 7326	Pass
Evaporation (99°C, 22h)(%)	GB/T 7325	1.4
Penetration after 100,000 times stroke (0.1mm)	GB/T 269	267
Water washout (38°C, 1h)(%)	SH/T 0109	1.1

PACKAGING 24X1LB





Informasi Produk

COBRA CALCIUM MULTIPURPOSE GREASE MERIGOLD NO 3

COBRA CALCIUM MULTIPURPOSE GREASE MERIGOLD NO 3 merupakan pilihan yang tepat untuk mendukung berbagai aplikasi operasional dalam memberikan perlindungan serta kinerja yang tahan lama.

PENGUNAAN

COBRA CALCIUM MULTIPURPOSE GREASE MERIGOLD NO 3 adalah gemuk serbaguna berbahan kalsium dengan konsistensi tinggi, di formulasikan secara khusus untuk memberikan pelumasan yang handal dan perlindungan yang luar biasa untuk berbagai aplikasi seperti mesin industri, konstruksi, otomotif serta mesin pertanian. Produk ini memiliki titik leleh pada suhu 147°C.

KEUNGGULAN

- Minimum titik leleh pada suhu 147°C
- Unggul dalam memberikan perlindungan terhadap korosi
- Memiliki tekstur halus yang lebih tahan lama
- Kental dan tidak mudah merubah bentuk (meleleh)
- Serbaguna untuk berbagai aplikasi
- Kemampuan kinerjanya setara dengan 70% kinerja *Lithium Grease*
- Memiliki karakteristik warna *Translucent Golden*

TYPICAL PROPERTY

CHARACTERISTIC	METHOD	RESULTS
Thickener		Calcium
Color Visual		Translucent Gold
Texture		Smooth
NLGI Consistency		3
Worked Cone Penetration (25°)(0.1mm)	GB/T 269	225
Dropping Point (°C)	GB/T 4929	147
Steel mesh oil separation (%)	SH/T 0324	1.3
Copper corrosion (100°C, 24h)	GB/T 7326	Pass
Evaporation (99°C, 22h)(%)	GB/T 7325	1.4
Penetration after 100,000 times stroke (0.1mm)	GB/T 269	267
Water washout (38°C, 1h)(%)	SH/T 0109	1.1

KEMASAN

24X1LB

